Kiro Spec-Driven Development

Version 2026 · verified 2026-11-09

Spec-driven development in Kiro — requirements, design, and tasks files, EARS, workflows, task runs, steering, and best practices.

Video walkthrough — scan the code to watch.

Contents

Mental model 3

The three spec files 3

Choose how much process 5

Requirements-First or Design-First 7

Write requirements in EARS 8

Bugfix specs 10

Run the tasks 11

Keep the spec in sync 13

Steering: standing context 14

Share and import specs 16
Further reading 17

Mental model

In Kiro, the spec is the durable artifact and the code is derived from it. A prompt becomes three Markdown files — what to build, how to build it, and the steps — and you approve each one before the next is generated. A wrong sentence in a requirement costs seconds to fix; the same mistake found in generated code costs a rewrite. Chat history disappears, but a spec is version-controlled, reviewable, and still there when the feature changes.

The three spec files

File	Answers	Contains
`requirements.md`	What	User stories, acceptance criteria
`bugfix.md`	What is broken	Current, expected,

File	Answers	Contains
		unchanged behavior
`design.md`	How	Architecture, data flow, interfaces
`tasks.md`	In what order	Discrete, trackable tasks

Every spec is a folder under `.kiro/specs/` named after the feature. A feature spec starts with `requirements.md`; a bugfix spec has `bugfix.md` in its place. The phases run in order — requirements (or bug analysis), design, tasks — and each file is generated from the ones you already approved.

```
.kiro/
  specs/
    user-authentication/
      requirements.md
```

```
    design.md
    tasks.md
steering/
  product.md
  tech.md
  structure.md
```

> **Tip:** Write one spec per feature, never one for the whole codebase. Focused specs stay readable, and teammates can work on different features without conflicts.

Choose how much process

Mode	Use when	Saves files
Vibe (chat)	Typos, one-line fixes, exploring	No
Plan mode	15–60 minute, multi-file change	No

Mode	Use when	Saves files
Quick Spec	Well-understood feature, prototype	Yes
Feature Spec	Unfamiliar or high-stakes feature	Yes
Bugfix Spec	Critical path, unclear root cause	Yes

Pick the lightest mode that still catches your mistakes. Plan mode asks structured questions, explores the codebase read-only, and hands a plan to the agent, but the plan lives only in the conversation. Quick Spec asks its clarifying questions up front, then generates all three files with no approval gates. A standard Feature Spec stops for your review after each file.

```
# From a vibe session, promote to a spec:
Generate spec
```

> **Gotcha:** Quick Spec output was never reviewed by a human. Its files have the same format as a standard spec's, so read `requirements.md` before you run the tasks.

Requirements-First or Design-First

	Requirements-First	Design-First
Start from	System behavior	Architecture, pseudocode
Order	Requirements, design, tasks	Design, requirements, tasks
Best for	Product-driven features	Strict technical constraints

Choose Requirements-First when you know the behavior you want and the architecture is free to follow. Choose Design-First when a design already exists, or when latency, throughput, or compliance limits decide

what is feasible — requirements are then derived from the design, so they are achievable by construction. Design-First also accepts diagrams: export a PNG or JPG, or photograph a whiteboard, and include it in the first prompt.

```
Create an MCP server for our data lake.
Must use FastAPI. Target: <100ms p95 query
latency. No UI components - pure API server.
```

> **Gotcha:** You cannot switch workflow after the spec is created. Start a new spec with the other workflow and copy over what still applies. Running both is fine: Design-First to prove feasibility, then Requirements-First for the full feature.

Write requirements in EARS

Part	Role
`WHEN`	The condition or event

Part	Role
`THE SYSTEM SHALL`	The observable behavior

`requirements.md` uses EARS (Easy Approach to Requirements Syntax). Each line pairs one trigger with one behavior, which makes it unambiguous, directly testable, and traceable to a task. Write one line per case, including the failure cases — a missing error path here becomes missing code later.

```
WHEN a user submits valid registration data
THE SYSTEM SHALL create a new user account

WHEN a user submits an email that already
exists
THE SYSTEM SHALL display an "Email already
registered" error
```

> **Tip:** Before design, run **Analyze Requirements** (IDE and CLI). It reasons across the whole set to find contradictions, vague terms such as “fast” or “large files”, and missing edge cases. It takes minutes, so skip it for small specs.

Bugfix specs

Section of `bugfix.md`	Pattern
Current behavior	`WHEN … THEN the system …`
Expected behavior	`… THEN the system SHALL …`
Unchanged behavior	`… SHALL CONTINUE TO …`

A bugfix spec records what is broken, what correct looks like, and what must not change. The third section is the point: it scopes the fix and turns “don’t break anything” into testable statements. Kiro then finds the root cause in `design.md` and generates tasks that reproduce the bug, fix it, and check for regressions.

```
When a user submits a form with special
characters in the name field (e.g. O'Brien),
the API returns a 500 error. It should accept
the input and save it correctly. Validation
for email and password must not change.
```

A good bug prompt has four parts: reproduction steps, current behavior, expected behavior, and constraints. If the fix turns out to need new functionality, open a separate Feature Spec — a bugfix spec cannot be converted.

> **Note:** Use a bugfix spec when the bug is on a critical path, the cause is unclear, or an earlier fix regressed. A typo or obvious one-liner belongs in chat.

Run the tasks

Action	IDE	CLI
New spec	`+` under **Specs**	`/spec new <name>`

Action	IDE	CLI
Run tasks	**Run all Tasks**	`/spec run <name>`
Open a file	Click it	`/spec view <name>`
List specs	**Specs** pane	`/spec`

Run tasks one at a time or all at once; `tasks.md` shows each task as in progress or completed as Kiro works. **Run all Tasks** builds a dependency graph and groups independent tasks into waves: tasks inside a wave run concurrently, and waves run one after another. No configuration is needed.

```
/spec new checkout
/spec run checkout
/spec view checkout requirements
/spec analyze_requirements checkout
```

Kiro can derive property-based tests from your EARS lines: one rule (“for any user and any car…”) checked against hundreds of generated inputs, then shrunk to

the smallest failing case. In the Kiro IDE these tests appear as tasks linked to the requirement they validate.

> **Gotcha: Run all Tasks** runs only incomplete tasks marked required. Property-based tests are optional by default, so a finished run does not mean they ran.

Keep the spec in sync

Change	Do this
New requirement	Edit `requirements.md`, or ask in a spec session
Design now stale	Ask Kiro to update `design.md`
Tasks now stale	**Sync Files** in `tasks.md`
Work done elsewhere	**Sync Files** marks tasks complete

A spec is meant to be revised, not written once. Change the upstream file first, then bring the downstream files back in line: requirements, then design, then **Sync Files**

to create tasks for what is new. In a Design-First spec the order is design, then requirements, then **Sync Files**.

```
#spec:user-authentication implement task 2.3
#spec:user-authentication does my code meet
the acceptance criteria for task 7.1?
```

`#spec` adds all three files of a spec to a chat message. Type `#spec` and press Enter to pick one. Use it to implement a task, validate finished work against the acceptance criteria, or ask why a design decision was made.

> **Warning:** Editing code without updating the spec makes the spec wrong, and the next task Kiro runs is generated from it. Fix the spec first.

Steering: standing context

`inclusion`	Loaded
`always` (default)	Every interaction

`inclusion`	Loaded
`fileMatch`	Files match `fileMatchPattern`
`manual`	You type `#file-name`
`auto`	Request matches `description`

Steering files are Markdown in `.kiro/steering/` (workspace) or `~/.kiro/steering/` (global). They hold what every spec should already know, so you do not repeat it in each prompt: `product.md` for purpose and users, `tech.md` for the stack, `structure.md` for layout and naming. Kiro also reads `AGENTS.md`, which is always included.

```
---
inclusion: fileMatch
fileMatchPattern: "components/**/*.tsx"
---
```

Link live files with `#[[file:api/openapi.yaml]]` so steering never goes stale by copy-paste. Keep one

domain per file, explain why a rule exists, and review steering changes like code.

> **Gotcha:** The front matter must be the first thing in the file — no blank line before it — or the inclusion mode is not applied. `auto` also requires `name` and `description`.

Share and import specs

Need	Approach
Share with your team	Commit `.kiro/specs/` with the code
Share across teams	Central repo plus Git submodules
Requirements in Jira	Connect its MCP server
Requirements in a doc	Copy to the repo, reference it

Specs are plain files, so they travel through pull requests like code and get reviewed the same way. For requirements that already exist elsewhere, either

connect an MCP server for that tool, or copy the document into the repository and point a spec session at it.

```
#foo-prfaq.md Generate a spec from it
```

Shared specs across several repositories can also use package references or symbolic links. On Kiro Web, one spec session can select multiple repositories, and the agent opens a pull request when the tasks finish.

> **Warning:** Steering and specs are part of the codebase. Never put API keys, passwords, or other secrets in them.

Further reading

- Specs overview — files, phases, and task execution on each surface
- Specs best practices — the official FAQ this sheet condenses

- Feature Specs — both workflows and EARS notation
- Bugfix Specs — the three behavior sections
- Correctness with property-based tests — properties, shrinking, limitations
- Steering — scopes, inclusion modes, file references